

(43) International Publication Date 21 December 2000 (21.12.2000)

PCT

(10) International Publication Number WO 00/77556 A1

(51) International Patent Classification⁷: G02B 26/00, 27/10

(21) International Application Number: PCT/US00/16023

(22) International Filing Date: 9 June 2000 (09.06.2000)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/138,865 60/173,659 11 June 1999 (11.06.1999) US 30 December 1999 (30.12.1999) US

(71) Applicant (for all designated States except US): UNIVER-SITY OF HAWAII [US/US]; Office of Technology Transfer and Economic Development, 2800 Woodlawn Drive, Suite 280, Honolulu, HI 96822 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): CHIAO, Jung, Chih [—/US]; 2505 Looktout Drive, Apt. 11208, Garland, TX 75044 (US).

- (74) Agent: SHERIDAN, James, A.; Flehr, Hohbach, Test, Albritton & Herbert L.L.P., Suite 3400, 4 Embarcadero Center, San Francisco, CA 94111-4187 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).


Published:

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

[Continued on next page]

(54) Title: MEMS OPTICAL COMPONENTS



(57) Abstract: An optical network (100), an optical device, and one or more MEMS optical components (105, 106) are disclosed. The optical network comprises one or more optical input sources (101), one or more optical output collectors (102), and the optical device. The optical device is optically coupled between the one or more optical input sources and the one or more optical output collectors. The optical device is formed on an integrated MEMS chip (104). The optical device comprises the one or more MEMS optical components formed on the integrated MEMS chip. In fact, each MEMS optical component may be monolithically fabricated on, self assemblable on, and reconfigurable or moveable on the integrated MEMS chip.

177556 A1